

MEDICAL 16 - 22 - 33 - 44



	MEDICAL 16	MEDICAL 22	MEDICAL 33	MEDICAL 44	
TYPE					TYPE
Capacité (rapport 1/10)	16 kg / 35.2 lbs	22 kg / 48.4 lbs	33 kg / 72.6 lbs	44 kg / 96.8 lbs	Load capacity (1.10 filling factor)
TAMBOUR					DRUM
Construction	Inox / stainless steel 304	Inox / stainless steel 304	Inox / stainless steel 304	Stainless steel AISI 304	Material
Diamètre	633 mm / 24.92 inches	633 mm / 24.92 inches	800 mm / 31.49 inches	800 mm / 31.49 inches	Diameter
Longueur	500 mm / 19.68 inches	700 mm / 27.56 inches	654 mm / 25.75 inches	870 mm / 34.25 inches	Length
Volume	158 dm ³	220 dm ³	330 dm ³	440 dm ³	Volume
Nb Compartiments	1	1	1	1	Nb of pockets
VITESSE TAMBOUR					DRUM SPEED
Lavage T/MN	45	45	45	45	Washing RPM
Essorage T/MN	1000	1000	1000	1000	Spin RPM
Facteur G	361	361	448	448	G Force
PORTE					PORTE
Ouverture tambour	400 x 315 mm	400 x 315 mm	450 x 320 mm	450 x 320 mm	Drum opening
Hauteur chargement	15.74 x 12.2 inches	15.74 x 12.2 inches	17.71 x 12.59 inches	17.71 x 12.59 inches	Height of loading
	680 mm / 20.37 inches	680 mm / 20.37 inches	780 mm / 30.70 inches	780 mm / 30.70 inches	
CHAUFFAGE ELECTRIQUE					ELECTRIC HEATING
Puissance chauffage	12 kw	18 kw	27 kw	33 kw	Heating power
Puissance moteur	2.2 kw	2.2 kw	4 kw	4 kw	Motor power
Puissance installée	14.2 kw	20.2 kw	31 kw	37 kw	Total required power
Consommation élect.	1.62 kw/h	2.42 kw/h	3.83 kw/h	4.43 kw/h	Electric consump.
ALIM. ELECTRIQUE	400/50-60/3+N	400-50-60/3+N	400/50-60/3+N	400/50-60/3+N	ELECTRIC SUPPLY
CHAUFFAGE VAPEUR					STEAM HEATING
Pression de travail	2 - 5 bars	2 - 5 bars	2 - 5 bars	2 - 5 bars	Working pressure
Consommation vapeur	1.2 kg / cycle	1.8 kg / cycle	2.4 kg / cycle	3.6 kg / cycle	Steam Output
Entrée vapeur	3/4"	3/4"	3/4"	3/4"	Steam inlet
Puissance électrique	2.2 kw	2.2 kw	4 kw	4 kw	Required elect. power
ALIMENTATION VAPEUR	230/50-60/1	230/50-60/1	400/50-60/3+N	400/50-60/3+N	STEAM SUPPLY
ALIMENTATION EAU					WATER SUPPLY
Nombre	3	3	3	3	Quantity
Pression de travail	3 - 5 bars	3 - 5 bars	3 - 5 bars	3 - 5 bars	Working pressure
Diamètre entrée eau	3/4"	3/4"	3/4"	3/4"	Water inlet diameter
Diamètre vidange	1 x 80 mm (3.14 inches)	1 x 80 mm (3.14 inches)	1 x 80 mm (3.14 inches)	1 x 80 mm (3.14 inches)	Drain diameter
CONSOMMATION EAU	9 lt/kg	9 lt/kg	9.7 lt/kg	9.7 lt/kg	WATER CONSUMP.
NIVEAU SONORE	65 db	65 db	65 db	65 db	NOISE LEVEL
DIMENSIONS					DIMENSIONS
Longueur	980 mm / 38.58 inches	1180 mm / 45.45 inches	1276 mm / 50.19 inches	1356 mm / 53.38 inches	Length
Profondeur	910 mm / 35.82 inches	910 mm / 35.82 inches	1056 mm / 41.57 inches	1056 mm / 41.57 inches	Depth
Hauteur	1385 mm / 54.52 inches	1385 mm / 54.52 inches	1580 mm / 62.20 inches	1580 mm / 62.20 inches	Height
Poids net	429 kg / 946 lbs	450 kg / 992 lbs	742 kg / 1636 lbs	816 kg / 1799 lbs	Net weight
EMBALLAGE					SHIPPING DIM.
Longueur	1124 mm / 44.25 inches	1324 mm / 52.12 inches	1420 mm / 55.90 inches	1500 mm / 59 inches	Length
Profondeur	1094 mm / 43.07 inches	1094 mm / 43.07 inches	1300 mm / 51.17 inches	1300 mm / 51.18 inches	Depth
Hauteur	1504 mm / 59.21 inches	1504 mm / 59.21 inches	1720 mm / 67.71 inches	1720 mm / 67.72 inches	Height
Poids brut	457 kg / 1007 lbs	473 kg / 1043 lbs	772 kg / 1701 lbs	846 kg / 1865 lbs	Gross weight